



NTN BEARING MANUFACTURING DE MEXICO,S...

2 Inch | 50.8 Millimeter x 2.189 Inch | 55.601
 Millimeter x 2.5 Inch | 63.5 Millimeter SKF P2B
 200-TF Pillow Block Bearings



P2B 200-TF Bearing 2D drawings and 3D CAD models

Bearing No. P2B 200-TF

Category	Pillow Block Bearings
Inventory	2.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	3.84
EAN	7316577345516
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-Expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	YAR 211-200-2F
Seals	Single Lip Contact
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Flinger Seal
Long Description	2 Bolt Pillow Block; 2" Bore; 2-1/2" Base to Center Height; Set Screw Mount; Ball Bearing; Relubricatable; Cast Iron; Single Lip Contact; Non-expansion



NTN BEARING MANUFACTURING DE MEXICO,S...

Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Weight / LBS	8.1585
Bolt Spacing Minimum	6.469 Inch 164.313Millimeter
d	2 Inch 50.8 Millimeter
D	2.189 Inch 55.601 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
Bolt Spacing Maximum	6.969 Inch 177.013Millimeter
Nominal Bolt Center to Center	6.7 Inch 170.2 Millimeter
B	2.5 Inch 63.5 Millimeter
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bore diameter:	2.0000 in
overall width:	2-3/16 in
bore type:	Round
radial dynamic load capacity:	9810 lbf
base to bore centerline:	2.5000 in
radial static load capacity:	6530 lbf
duty type:	Normal Duty
base width:	60 mm
housing material:	Cast Iron
bolt center-to-center length:	171.5 mm
locking device:	Set Screw
maximum rpm:	3600 RPM



NTN BEARING MANUFACTURING DE MEXICO,S...

seal type:	Contact/Lip
lubrication type:	Lubrication Fitting
expansion type:	Non-Expansion Bearing (Fixed)
series:	SY
overall length:	219 mm
replacement bearing:	YAR 204-2F
overall height:	126 mm
standards met:	ISO