



NTN BEARING MANUFACTURING DE MEXICO,S...

2.5 Inch | 63.5 Millimeter x 2.689 Inch | 68.301 Millimeter x 3 Inch | 76.2 Millimeter SKF P2B 208-TF Pillow Block Bearings



P2B 208-TF Bearing 2D drawings and 3D CAD models

Bearing No. P2B 208-TF

Category	Pillow Block Bearings
Inventory	4.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	5.75
EAN	7316577345530
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-Expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	YAR 213-208-2F
Seals	Single Lip Contact
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Flinger Seal
Long Description	2 Bolt Pillow Block; 2-1/2" Bore; 3" Base to Center Height; Set Screw Mount; Ball Bearing; Relubricatable; Cast Iron; Single Lip Contact; Non-expansion



NTN BEARING MANUFACTURING DE MEXICO,S...

Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Weight / LBS	14.00175
D	2.689 Inch 68.301 Millimeter
d	2.5 Inch 63.5 Millimeter
Bolt Spacing Maximum	8.437 Inch 214.3Millimeter
Bolt Spacing Minimum	7.563 Inch 192.1Millimeter
Nominal Bolt Center to Center	8 Inch 203.2 Millimeter
B	3 Inch 76.2 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bore diameter:	2.5000 in
overall width:	2-11/16 in
bore type:	Round
radial dynamic load capacity:	12870 lbf
base to bore centerline:	3.0000 in
radial static load capacity:	9000 lbf
duty type:	Normal Duty
base width:	65 mm
housing material:	Cast Iron
bolt center-to-center length:	203 mm
locking device:	Set Screw
maximum rpm:	3000 RPM
seal type:	Contact/Lip



NTN BEARING MANUFACTURING DE MEXICO,S...

lubrication type:	Lubrication Fitting
expansion type:	Non-Expansion Bearing (Fixed)
series:	SY
overall length:	257 mm
replacement bearing:	YAR 213-208-2F
overall height:	151 mm
standards met:	ISO